

Grillage Soudé

Matière

Inox 316L / 304L

Diamètre de fil en mm

3

Vide de maille en mm (L x l)

25 x 25

Format en mm

2000 x 1000

Poids unitaire en kg

9

Conditionnement


En panneaux

Numéro article

380292M

Tolérances

- Format : +/- 35 mm
- Maille : -10% / + 5%
- Diamètre de fils : - 10% / + 0%



Le grillage soudé qualité serrurerie est précis, robuste et se prête aisément aux travaux de pliage et de cintrage.

Atouts : Très grande régularité des mailles, multiples facilités d'emploi, solidité remarquable.

Utilisations : Volières, armatures, panneaux isolants, protection, séparations faux plafonds, rayonnages, enclos et chassis divers...

Weld Mesh

Raw material

Stainless steel 316L / 304L

Wire diameter in mm

3

Mesh vacuum in mm (L x I)

25 x 25

Size in mm

2000 x 1000

Unit weight in kg

9

Packing


In panels

Item number

380292M

Tolerances

- Size : +/- 35 mm
- Mesh : -10% / + 5%
- Wire diameter : - 10% / + 0%



High quality precision weldmesh is accurate, robust, malleable. It can be rolled and / or folded.

Features : Very accurate mesh dimensions, versatile, high strength.

Uses : Aviaries, reinforcing insulation panels, protection, partitions, suspended ceilings, shelves, enclosures and gabions.